Newport Butane Refill

Revision: 1

Revision date: 08.03.2018

Manufactured in the UK



According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Newport Butane Refill
Container size 90mL, 250mL, 300mL, 400mL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesTo be used for refilling butane-powered domestic products

Uses advised against Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier Keen-Newport Global Limited

Unit 31 Kingfisher Court

Newbury Berkshire RG14 5SJ

1.4. Emergency telephone number

Emergency telephone +44 (0)1635 34600 (Mon-Fri 09:00-17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Not Classified Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P102 Keep out of reach of children.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

Newport Butane Refill

Revision date: 08.03.2018 Revision: 1



SECTION 3: Composition/information on ingredients

3.2. Mixtures

butane 30-60%

CAS number: 106-97-8 EC number: 203-448-7 REACH registration number: 01-

2119474691-32-XXXX

Contains no other substances or impurities which will influence the classification of the product.

Classification (67/548/EEC or 1999/45/EC) Classification

Flam. Gas 1 - H220 F+; R12. Extremely flammable.

Press. Gas (Liq.) - H280

isobutane 10-30%

CAS number: 75-28-5 EC number: 200-857-2 REACH registration number: 01-

2119485395-27-0000

Contains no other substances or impurities which will influence the classification of the product.

Classification Classification (67/548/EEC or 1999/45/

Flam. Gas 1 - H220 F+; R12. Extremely flammable.

Press. Gas (Liq.) - H280

10-30% propane

CAS number: 74-98-6 EC number: 200-827-9 REACH registration number: 01-

2113486944-21-0000

Contains no other substances or impurities which will influence the classification of the product.

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+; R12. Extremely flammable.

Press. Gas (Liq.) - H280

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information 'If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms

are severe or persist.

Ingestion Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not

induce vomiting unless under the direction of medical personnel.

Skin contact Rinse with water.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical

attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

Revision date: 08.03.2018

Newport Butane Refill

Revision: 1

Manufactured in the UK



General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing

media

The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire.

media

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

> Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and

propellant. Vapours may form explosive mixtures with air.

Hazardous combustion

Products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

5.3. Advice for firefighters

Firefighting

Protective actions during Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs,

notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Newport Butane Refill

Revision date: 08.03.2018 Revision: 1

Manufactured in the UK



Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters Occupational exposure limits

butane

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

isobutane

800ppm (TWA/TLV)

propane

TLV (ACGHIH) - 1.000 ppm

Newport Butane Refill

Revision: 1

Manufactured in the UK



WEL = Workplace Exposure Limit

8.2. Exposure controls

Revision date: 08.03.2018

Appropriate engineering Provide adequate ventilation.

controls

Eye/face protection Avoid contact with eyes. Large Spillages: Eyewear complying with an approved standard

should be worn if a risk assessment indicates eye contact is possible.

Hand protection No specific hand protection recommended.

Hygiene measures Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

Wash contaminated clothing before reuse.

Respiratory protection No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is

inadequate, suitable respiratory protection must be worn.

Environmental exposure Keep container tightly sealed when not in use. Avoid release to the environment.

controls

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Colourless.

Odour Natural gas

pH No information available.

Melting point -11°C

Initial boiling point and rangeNo information available.Flash pointNo information available.Evaporation rateNo information available.Flammability (solid, gas)No information available.Upper/lower flammability or explosive limitsNo information available

Vapour pressure 2.73 Bar @ 20°C

Vapour density No information available. **Relative density** No information available. Solubility(ies) No information available. **Partition coefficient** No information available. **Auto-ignition temperature** No information available. No information available. **Decomposition Temperature** No information available. Viscosity **Explosive properties** No information available.

Explosive under the Influence of a flame Yes

Oxidising properties Not available.

Newport Butane Refill

Revision: 1

Manufactured in the UK



9.2. Other information

Revision date: 08.03.2018

Other information Gas/vapour heavier than air. May accumulate in confined spaces, particular at or below

ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous The following materials may react strongly with the product: Oxidising agents.

reactions

Products

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised

container: may burst if heated

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition Does not decompose when used and stored as recommended. Thermal decomposition or

combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Newport Butane Refill

Revision date: 08.03.2018 Revision: 1 Manufactured in the UK



Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Repeated exposure may cause skin dryness or cracking. **Eve contact** May be slightly irritating to eyes. May cause discomfort.

Route of exposure Ingestion Inhalation Skin and/or eye contact

No specific target organs known. **Target organs**

Toxicological information on ingredients.

butane

Acute toxicity - oral

Notes (oral LD₅₀) Technically not feasible.

Acute toxicity - dermal

Technically not feasible. Notes (dermal LD₅₀)

Acute toxicity - inhalation

Acute toxicity inhalation

1,443.0

(LC₅₀ vapours mg/l)

Rat **Species**

ATE inhalation (vapours mg/I) 1,443.0

Skin corrosion/irritation

Skin corrosion/irritation Technically not feasible.

Serious eye damage/irritation

Serious eye damage/irritation Technically not feasible.

Respiratory sensitisation

Revision date: 08.03.2018

Newport Butane Refill

Revision: 1

Manufactured in the UK



Respiratory sensitisation Data lacking

Skin sensitisation

Skin sensitisation Technically not feasible.

Germ cell mutagenicity

Genotoxicity - in vitro Negative. **Genotoxicity - in vivo** Negative.

Carcinogenicity

Carcinogenicity Data lacking.

isobutane

Acute toxicity - oral

Notes (oral LD₅₀) Technically not feasible.

Acute toxicity - dermal

Notes (dermal LD₅₀) Technically not feasible.

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ gases ppmV)

800,000.0

Species Rat

ATE inhalation (gases ppm) 800,000.0

Skin corrosion/irritation

Skin corrosion/irritation Technically not feasible.

Serious eye damage/irritation

Serious eye damage/irritation Technically not feasible.

Respiratory sensitisation

Respiratory sensitisation Data lacking.

Skin sensitisation

Skin sensitisation Technically not feasible.

Germ cell mutagenicity

Genotoxicity - in vitro Negative. **Genotoxicity - in vivo** Negative.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Specific target organ toxicity - single exposure
STOT - single exposure
Not classified

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified

Newport Butane Refill

Revision: 1

Revision date: 08.03.2018

Manufactured in the UK



Inhalation Irregular cardiac activity.

propane

Acute toxicity - oral

Notes (oral LD₅₀) Technically not feasible.

Acute toxicity - dermal

Notes (dermal LD₅₀) Technically not feasible.

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

1,443.0

Species Rat

ATE inhalation (vapours mg/l) 1,443.0

Skin corrosion/irritation

Skin corrosion/irritation Technically not feasible.

Serious eye damage/irritation

Serious eye damage/irritation Technically not feasible.

Respiratory sensitisation

Respiratory sensitisation Data lacking.

Skin sensitisation

Skin sensitisation Technically not feasible.

Germ cell mutagenicity

Genotoxicity - in vitro Negative. **Genotoxicity - in vivo** Negative.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Reproductive toxicity

Reproductive toxicity – fertility Screening - NOAEC 3.000 ppm, Inhalation, Rat

Reproductive toxicity – development Developmental toxicity: - NOAEC: 9.000 ppm, Inhalation,

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients.

Newport Butane Refill

Revision: 1

Revision date: 08.03.2018

Manufactured in the UK



Butane

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 49.9 mg/l, Fish

Acute toxicity - aquatic

Invertebrates

LC₅₀, 48 hours: 69.43 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: 19.37 mg/l, Algae

Isobutene

Toxicity The product is not believed to present a hazard due to its physical nature.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 49.9 mg/l, Fish

Acute toxicity - aquatic

invertebrates

LC₅₀, 48 hours: 69.43 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: 19.37 mg/l, Algae

Propane

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 49.9 mg/l, Fish

Acute toxicity - aquatic

Invertebrates

LC₅₀, 48 hours: 69.43 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: 19.37 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Butane

Phototransformation Air - DT₅₀: 1906 days

Biodegradation Water - Degradation 100: 385.5 hours

Isobutene

Persistence and degradability

Biodegradation

Not applicable.

Water - Half-life 100: 6,9 days

Propane

Phototransformation

Biodegradation

Air - DT₅₀ : 1906 days

Water - Degradation 100: 385.5 hours

Page **10** of **15**

Revision date: 08.03.2018

Newport Butane Refill Revision: 1



12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

butane

Bioaccumulative potential **Partition coefficient**

The product does not contain any substances expected to be bioaccumulating.

log Pow: 2,89

isobutane

Bioaccumulative potential **Partition coefficient**

Because of the low log kow, accumulation in organisms is not to be expected.

log Pow: ~ 2,76

propane

Bioaccumulative potential Partition coefficient

Because of the low log kow, accumulation in organisms is not to be expected.

log Pow: ~ 3

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

Ecological information on ingredients.

butane

Mobility No data.

isobutane

Mobility No data.

propane

Mobility No data.

12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

butane

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

isobutane

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

propane

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Page 11 of 15

Revision date: 08.03.2018

Revision: 1

Newport Butane Refill



Manufactured in the UK

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle

> products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product

residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Empty containers must not be punctured or incinerated because of

the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with

the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS Proper shipping name (IMDG) **AEROSOLS** Proper shipping name (ICAO) **AEROSOLS** Proper shipping name (ADN) **AEROSOLS**

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

14.5. Environmental hazards

Newport Butane Refill

Revision: 1 Manufactured in the UK



Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2
Tunnel restriction code (D)

Revision date: 08.03.2018

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IATA: International Air Transport Association.

ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate.

LC₅₀: Lethal Concentration to 50 % of a test population.

LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).

 EC_{50} : 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

Revision date: 08.03.2018

Newport Butane Refill Manufactured in the UK

Classification abbreviations

and acronyms

Revision: 1

Aerosol = Aerosol

Classification procedures according to Regulation (EC)

1272/2008

Aerosol 1 - H222, H229: : Expert judgement.

Read and follow manufacturer's recommendations. **Training advice**

Revision date 08/03/2018

Revision 1 **SDS** number 4856

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

Newport Butane Refill

Revision: 1

Revision date: 08.03.2018

Manufactured in the UK



This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.